

BA Optima

Contra-angle and Straight (no light/no spray)

Made in Austria



Superior, ergonomic and smooth design. Made in Austria.

BA60E 4:1



KEY FACTS:

- Screw-in prophy contra-angle.
- 4:1 ratio.
- No light.
- No spray.
- Thermoisinfectable.
- Autoclavable.



Model	Code	Description
BA60E	BA611075	Screw in prophy 4:1

BA40E 1:1



KEY FACTS:

- Push button contra-angle.
- 1:1 direct ratio.
- No light.
- No spray.
- Thermoisinfectable.
- Autoclavable.
- Easy to clean.



Model	Code	Description
BA40E	BA611074	Push button direct 1:1

BA170E 1:1



KEY FACTS:

- Straight handpiece.
- 1:1 ratio.
- No light.
- No spray.
- Thermoisinfectable.
- Autoclavable.

Model	Code	Description
BA170E	BA620070	Straight 1:1

BA Ultimate & Optima Air Motors

BA602/BA604 Optima



BA602S/BA604S Ultimate



KEY FACTS:

- Available in Midwest and Borden fittings.
- Fits standard or short contra-angles.
- No light.
- Forward/reverse directional control.
- Thermoisinfectable and autoclavable.
- Speed range: 5,000-25,000 rpm (3 bar).


BA602/BA604 Optima (external spray)

Model	Code	Description
BA602	BA640081	2 hole Borden, external spray
BA604	BA640060	4 hole Midwest, external spray

BA602S/BA604S Ultimate (internal spray)

Model	Code	Description
BA602S	BA641080	2 hole Borden, internal spray
BA604S	BA641060	4 hole Midwest, internal spray

Fittings



BA604L Ultimate

KEY FACTS:

- Air motor with internal spray.
- Fibre-optic.
- Midwest fitting.
- Thermoisinfectable and autoclavable.
- Speed range: 5,000-25,000 rpm (3 bar).



Fittings



BA604L Ultimate

Model	Code	Description
BA604L	BA640560	6 hole Midwest, internal spray, with light